

National Fenestration
Rating Council®

CERTIFIED

GLASS CRAFT®

DOOR COMPANY

HARDWOOD ENTRY DOOR SERIES

CPD# - GDC - m1

Portobello / Estancia / Legacy

ENERGY PERFORMANCE RATINGS

PRODUCT DESCRIPTION*
Default Frame**
Wood

U-Factor / Solar Heat Gain Coefficient (SHGC)

Individual Option Number

 $\frac{1}{4}$ Lite
≤ 410†

 $\frac{2}{3}$ Lite
≤ 900†

 $\frac{3}{4}$ Lite
≤ 1100†

 Full Lite
≤ 1100†

SIDELITES

Double IG
Wrought Iron
 $\frac{0.51}{0.26}$
00033 - 00001

 $\frac{0.51}{0.30}$
00036 - 00001

 $\frac{0.50}{0.36}$
00039 - 00001
Triple IG
Decorative
 $\frac{0.45}{0.21}$
00034 - 00001

 $\frac{0.45}{0.25}$
00037 - 00001

 $\frac{0.45}{0.32}$
00040 - 00001

TDL / Low-E

 $\frac{0.41}{0.23}$
00034 - 00001

 $\frac{0.40}{0.27}$
00038 - 00001

 $\frac{0.40}{0.32}$
00041 - 00001
Flush / Embossed
00108-00001U-Factor **0.41** SHGC **0.02**

Air Leakage

cfm.ft

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product, and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.

* #glazing layers / spacer type / low-e emissivity (surface) / gap fill / gap width (na=not applicable)

** per NFRC 100

¹ W/m²*K (btu/hr²*F)

*** Numbers below the performance ratings are referenced in the NFRC Certified Products Directory

(e.g., ABC-X-1-00001-00001 or 123-X-1-00001-00001)

www.nfrc.org

